


FM293-3L-X

FM293-75L-X

GENTEC is proud to introduce our line of Neonatal, Perinatal and Specialty Flowmeters.

GENTEC Flowmeters are designed and manufactured to meet the highest standards of performance and accuracy for the applications of critical care on both neonate and adult patients. Models available for flowmeters from 200cc to 75LPM.

Features

- Available for oxygen and air with accuracy and performance.
- Acrylic block provides a strong and superior-looking flow tube.
- 200cc and 1LPM model are designed for perinatal and neonatal applications where extreme accuracy under very low flow is required.
- Precise flow control.
- Maximum Inlet Pressure: 100PSI.
- Inlet Connection: See table below (Models for additional inlet connections are available).
- Outlet: DISS Male (9/16"-18UNF).
- Calibrated at 50PSI.
- 5-Year warranty (see warranty statement for details).

Ordering Information & Specification

| Inlet Fitting (Back Fitting) | Maximum Flow Rate Scale / Gas Service | | | | | | |
|---------------------------------|---------------------------------------|-----------------|-----------------|------------------|------------------|----------------|----------------|
| | 200CC OXYGEN | 1 LPM OXYGEN | 3 LPM OXYGEN | 16 LPM OXYGEN | 75 LPM OXYGEN | 16 LPM AIR | 75 LPM AIR |
| 1/8NPTF | FM293-200CC-X | FM293-1L-X | FM293-3L-X | FM293-16L-X | FM293-75L-X | FM293-16L-Q | FM293-75L-Q |
| CHEMETRON | FM293-200CC-X-CH | FM293-1L-X-CH | FM293-3L-X-CH | FM293-16L-X-CH | FM293-75L-X-CH | FM293-16L-Q-CH | FM293-75L-Q-CH |
| DISS HEX | FM293-200CC-X-DS | FM293-1L-X-DS | FM293-3L-X-DS | FM293-16L-X-DS | FM293-75L-X-DS | FM293-16L-Q-DS | FM293-75L-Q-DS |
| DISS HANDTIGHT | FM293-200CC-X-DH | FM293-1L-X-DH | FM293-3L-X-DH | FM293-16L-X-DH | FM293-75L-X-DH | FM293-16L-Q-DH | FM293-75L-Q-DH |
| OHMEDA | FM293-200CC-X-OH | FM293-1L-X-OH | FM293-3L-X-OH | FM293-16L-X-OH | FM293-75L-X-OH | FM293-16L-Q-OH | FM293-75L-Q-OH |
| PURITAN- BENNETT | FM293-200CC-X-PB | FM293-1L-X-PB | FM293-3L-X-PB | FM293-16L-X-PB | FM293-75L-X-PB | FM293-16L-Q-PB | FM293-75L-Q-PB |
| OXEQUIP MEDSTAR | FM293-200CC-X-OE | FM293-1L-X-OE | FM293-3L-X-OE | FM293-16L-X-OE | FM293-75L-X-OE | FM293-16L-Q-OE | FM293-75L-Q-OE |

| | 200CC OXYGEN | 1 LPM OXYGEN | 3 LPM OXYGEN | 16 LPM OXYGEN | 75 LPM OXYGEN | 16 LPM AIR | 75 LPM AIR |
|-----------------|---|-----------------|---|---|-------------------------|---|-------------------------|
| Accuracy | ±10 cc from 25-100 cc ±15 cc form 100-200 cc | ±.05 lpm | ±.15 lpm from 1/4 to 2 lpm ±.25 lpm above 2 to 3 lpm | ±.25 lpm from 1/2 to 4 lpm ±.5 lpm above 6 to 15 | 5 lpm (starts at 5 lpm) | ±.25 lpm from 1/2 to 4 lpm ±.5 lpm above 6 to 15 | 5 lpm (starts at 5 lpm) |
| Flush Flow | 500cc | 5-10 lpm | 20-50 lpm | 60-90 lpm | 70-100 lpm | 60-90 lpm | 70-100 lpm |

• Outlet for all flowmeters are DISS Male (9/16"-18UNF). • ISO flowmeters are available. • Models with additional inlet connections are available.

GR-FLY-MEDFM2930413 V1

