

Flowmeter Regulators With Humidifiers



895M-15L

- Also available with CGA 870 inlet (895M-15LY)

Flow Gauge Regulators



230M-15Y

- Preset 50 psi outlet pressure; 3,000 psig maximum inlet pressure.
- 0-5, 0-8, 0-15 and 0-45 LPM flow ranges.
- CGA 870 (Yoke) or CGA 540 (Nut & Nipple) inlet connection.
- Chrome-plated brass body.

Flowmeter Regulators



191M-15L
OXYGEN

- 3,000 psig maximum inlet pressure.
- Back pressure compensated 0-15 LPM (0-12 for Heliox) flowmeters.
- CGA 870 (Yoke) or CGA 540 (Nut & Nipple) inlet connection.
- Chrome-plated brass body.



197HX-12L
HELIOX
(80/20)

5 year warranty (see warranty statement for details)



210M-15YR

- Chrome-plated brass body.
- Diaphragm-type regulator.
- Flow range: 0-15 LPM.
- CGA 870 inlet connection with filter.
- Oxygen DISS outlet connection.
- Maximum inlet pressure: 3,000 psig.
- 1.5" pressure gauge.

190M-15H

- Chrome plated brass body.
- 3000 psi maximum inlet pressure.
- 1.5" pressure gauge.
- Internal relief valve.
- Diaphragm-type regulator design.
- Dual scale pressure gauge PSI/KPI
- Adjustable flow setting.
- CGA 870 (Yoke) or CGA 540 (Nut & Nipple) inlet connection.
- Sintered brass inlet filter for longer service life.



Catalog # FLM-REG200809